

**Datasheet**
**Description**

The FEK-06 calibration kit provides accurate calibration of the Vector Network Analyzer (VNA) in WR-06 band. It is compatible with TRL and SOLT calibration techniques.


**Features**

- Ensures accurate and repeatable measurements
- Contains characterisation data for the kit components in a suitable format for the VNA

**Applications**

- Millimeter wave S-parameter measurements that require system error correction

Specification	Unit	Min	Typ	Max
Operating Frequency Range	GHz	110		170
Frequency Band		D		
Waveguide Designation		WR-06, WG-29		
Flange Type		UG387/U-PF (Precision style)		
Cut Off Frequency	GHz	90.76 GHz		
Fixed Load VSWR		< 1.04:1		
Flush Short Flatness	mm	< 0.006		
Operating Temperature Range	°C	+20		+30

Content	Q-ty
Fixed Termination	1 off
Sliding Termination	1 off
Flush Short	1 off
¼ Lambda Offset – Band 1	1 off
¾ Lambda Offset – Band 1	1 off
K – Section Offset	1 off
¼ Lambda + K Section Offset	1 off
<b>Accessories</b>	
Torque Hex Driver 5/64" A/F	1 off
Hex Driver – 1/8" A/F	1 off
Flange Screws -Short	8 off
Flange Screw - Long	8 off
Alignment Pins	8 off
USB Flash Memory	1 off

Note: Farran Technology reserves the right to change, without notice, the characteristic data and other specifications applied to this product. The product may be subject to Irish export

