

Datasheet
Description

The FEK-02 calibration kit provides accurate calibration of the Vector Network Analyzer (VNA) in WR-02 band. It is compatible with TRL and SOLT calibration techniques.


Features

- Ensures accurate and repeatable measurements
- Contains characterisation data for the kit components in a suitable format for the VNA

Applications

- Millimeter wave S-parameter measurements that require system error correction

Specification	Unit	Min	Typ	Max
Operating Frequency Range	GHz	325		500
Frequency Band		-		
Waveguide Designation		WR-02, WM-570		
Flange Type		IEEE 1785-2a (Precision style)		
Cut Off Frequency	GHz	262.90 GHz		
Fixed Load VSWR		< 1.08:1		
Flush Short Flatness	mm	< 0.012		
Operating Temperature Range	°C	+20		+30

Content	Q-ty
Fixed Termination	1 off
Sliding Termination	1 off
Flush Short	1 off
$\frac{3}{4}$ Lambda Offset – Band 1	1 off
$\frac{3}{4}$ Lambda Offset – Band 2	1 off
$\frac{3}{4}$ Lambda Offset – Band 3	1 off
K – Section Offset	1 off
$\frac{1}{4}$ Lambda + K Section Offset	1 off
Accessories	
Torque Hex Driver 5/64" A/F	1 off
Hex Driver – 1/8" A/F	1 off
Flange Screws -Short	8 off
Flange Screw - Long	8 off
Alignment Pins	8 off
USB Flash Memory	1 off

Note :

Datasheet

Farran Technology reserves the right to change, without notice, the characteristic data and other specifications applied to this product. The product may be subject to Irish export restrictions.