

AutoPoint Alignment System



HXI's AutoPoint System, designed exclusively for HXI Radios, provides mmWave radio path alignment from any remote location. It is the perfect solution to align and maintain high bandwidth directional antennas for many communication applications.

AutoPoint is a complete hardware and software solution. It can be used to "fine tune" initial alignment, and more importantly, can be used to re-align your link as required. The Web based user access makes it easy to optimize link performance regardless of the time of day, season, or current weather conditions.

FEATURES & BENEFITS

- Web based user interface for remote access
- Automated pan and tilt positioner (+/- 0.15° Accuracy)
- Integrated GPS and digital compass for auto acquisition
- Power over Ethernet (PoE)
- Maintenance free anodized aluminum

TECHNICAL SPECIFICATIONS

Power	Power Over Ethernet (PoE) 48 VDC Supply Included
Material/Finish	Aluminum with stainless steel hardware / Hard coat anodize
Travel Limits	
Azimuth / Elevation	440° (+/- 220°) / 20° (+/-10°)
Drive Rate	
Azimuth / Elevation	Variable, up to 4.5° per sec no load / Variable, up to 2° per sec no load
Temperature	
Operational / Survival	-22 to 140°F (-30 to 60°C) / -40 to 158°F (-40 to 70°C)
Pan / Tilt Repeatability	+/- 0.15°
Wind	
Operational / Survival	65 mph gusting to 80 mph / 100 mph
Dimensions (H * W * D)	15.2" * 8.7" * 10.6"
Weight	17.4 lbs
Mounting Interface	Clamps to 2" diameter mast
Antenna Mount Options	1 – 2 ft solid parabolic, 1 – 2 ft panel antenna, up to 3ft grid antenna

12 Lancaster County Road, Harvard, Massachusetts 01451 Tel: (978) 772-7774 FAX: (978) 772-7775

Visit us on the web at www.hxi.com